

Product Name	Name	REMAIN LUNAR A20	REMAIN Dawn A10
		Type2(IEC62196) & Type1(J1772)	
Product Photo	Photo		
Product Model	Model	RCD220/32-1OBG-B-7kW RCD380/16-1OBG-B-11kW	RCD380/16-1OBG-B-11kW RCD380/32-1OBG-B-22kW
Appearance	Dimensions	350MM*200MM*120MM	400*250*160MM
	Materials	ABS+PC material	ABS+PC material
Electrical Parameters	Charging type	Type2	Type 2
	Charging standard	IEC62196	IEC-62196
	Output power	7kW/11kW	11kW/22kW
	Output voltage	AC220V±15%/ single phase AC380V±15%/ three phase	AC380V±15%/ three phase
	Input voltage	AC220V±15%/ single phase AC380V±15%/ three phase	AC380V±15%/ three phase
	Rated frequency	50/60Hz	50/60Hz
	Max output current	0-32A/0-16A	0-16A/0-32A
	Cable length	5m	5m
	RCD protection	A+6(30 mA AC+6 mA DC)	A+6(30 mA AC+6 mA DC)
	User authentication	RFID/APP	RFID/APP
	Communication protocol	OCPP1.6J	OCPP1.6J
	RFID reader	Yes	Yes
Function Design	Payment method	QR code payment/Credit card payment	QR code payment/Credit card payment
	Charging method	Cable	Cable/Socket
	User interface	Card reader	Card reader
	Number of charging guns	Single cable	Single cable/Single socket
	Communication with EV	Ethernet, WIFI, 4G	MID meter
	Meter type	/	
Safety Design	IP grade	IP65	IP65
	Other protections	Moisture-proof,midew-proof,salt spray-proof	Moisture-proof,midew-proof,salt spray-proof
	Installation method	Wall/Stand	Wall/Stand
Environmental Indicators	Operation temperature	-30°C~+50°C	-30°C~+50°C
	Humidity	5% to 95%	5% to 95%
	Altitude	≤2000m	≤2000m